



MASTER INSTRUMENT CORPORATION

Schottky Barrier Rectifiers SR520 THRU SR5100


VOLTAGE RANGE 20 to 100 Volts
Forward Current 5.0 Amperes

FEATURES

- ! Fast switching
- ! Low forward voltage, high current capability.
- ! Low power loss high efficiency
- ! High current surge capability
- ! Fast switching for high efficiency
- ! High temperature soldering guaranteed:
250°C/10 second, at terminals

MECHANICAL DATA

- ! Case: Transfer molded plastic
- ! Terminal: UL94v-0 rate flame retardant
- ! Polarity: Color band denotes cathode end.
- ! Lead Plated axial lead ,solderable per MIL-STD-202E method
208C
- ! Mounting position: Any.
- ! Weight: 0.042 ounce 1.19 gram



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.

Single phase, half wave, 60Hz, resistive or inductive load.

For capacitive load derate current by 20%.

		SYMBOLS	SR520	SR530	SR540	SR550	SR560	SR580	SR590	SR5100	UNITS
Maximum Repetitive Peak Reverse Voltage		V _{RRM}	20	30	40	50	60	80	90	100	Volts
Maximum RMS Voltage		V _{RMS}	14	21	28	35	42	57	63	70	Volts
Maximum DC Blocking Voltage		V _{DC}	20	30	40	50	60	80	90	100	Volts
Maximum Average Forward Rectified Current, See Fig2		I _(AV)	5.0								Amps
Peak Forward Surge Current 8.3ms single half sine-wave superimposed on rated load (JEDEC Method)		I _{FSM}	150								Amps
Maximum Instantaneous Forward Voltage Drop per bridge element at 5A		V _F	0.55			0.70		0.80	0.85		Volts
Maximum DC Reverse Current at rated DC blocking voltage per element	T _A =25 °C	I _R	5.0								MAmps
	T _A =100 °C		50								
Typical Junction Capacitance (Note 2)		C _J	150								pF
Typical Thermal Resistance (Note 3)		R _{θJA}	25								°C/W
Operating and Storage Temperature Range		T _J	-65 to +125			-65 to +150					°C
Storage Temperature Range		T _{STG}	-65 to +150								°C

NOTES:

1. Pulse test: 300 us pulse width 1% duty cycle
2. Measured at 1.0 MHz and applied reverse voltage of 4.0 Volts.
3. Thermal resistance from junction to ambient P.C.B mounted with 0.375"(9.5mm) lead length with 1.5"X1.5"(38 X38mm) copper pads.



MASTER INSTRUMENT CORPORATION

Schottky Barrier Rectifiers
SR520 THRU SR5100

VOLTAGE RANGE 20 to 100 Volts
Forward Current 5.0 Amperes

RATINGS AND CHARACTERISTIC CURVES SR520 THRU SR5100

FIG.1-TYPICAL FORWARD CURRENT
DERATING CURVE




FIG.2-MAXIMUM NON-REPETITIVE PEAK
FORWARD SURGE CURRENT




FIG.3-TYPICAL INSTANTANEOUS
FORWARD CHARACTERISTICS




FIG.4-TYPICAL REVERSE
CHARACTERISTICS




FIG.5-TYPICAL JUNCTION CAPACITANCE

